

Paraffin Solvent & Dispersant

PHYSICAL DESCRIPTION

| | |
|------------------|---|
| Appearance | Clear, Colourless to Pale Yellow, free-flowing liquid |
| Freezing Point | < -40°C |
| Flash Point | -30°C (PMCC) |
| Specific Gravity | 0.65 – 0.76 |
| Solubility | Oil – Soluble |
| Odour | Hydrocarbon |

PROPERTIES

StaSolv™ 114 is our premier well optimization and wax solvent, composed only of refined, paraffin-free hydrocarbon products, and also contains a field-proven wax dispersant

StaSolv™ 114 is often recommended to treat wells with long chain wax deposits.

StaSolv™ 114 can be used to aid in cleaning up sludge and emulsions, workover fluids or as a heavy crude oil diluent.

StaSolv™ 114 will not alter natural wettability within downhole formations, but will penetrate fouling on formation surface and help remove waxy deposits.

BENEFITS

StaSolv™ 114 will soften and help remove paraffin deposits with chain lengths from C₁₆ to C₄₄₊, that collect on both down-hole and surface production equipment.

StaSolv™ 114 allows effective wetting of downhole surfaces; dispersant will act as a surface penetrant of paraffinic deposits.

Paraffin Solvent & Dispersant

MIXING & HANDLING INSTRUCTIONS

StaSolv™ 114 should be applied in neat form, typically with dosages of 1000 to 2000ppm in produced oil for continuous injection purposes.

StaSolv™ 114 can be applied on a continuous basis or batch application.

For maximum effectiveness, a shut period is recommended to assist in maximum paraffinic deposit removal if a batch application is used.

Improved overall stimulations will result when used in conjunction with a CFR Dispersant and Wax Inhibitor Package.

CAUTION

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation and causes eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Handle with care as with any industrial chemical.

Before using this product refer to the Safety Data Sheet for all safety and handling information.

StaSolv™ 114 is available in 20L pails, 205L drums, 1000L totes and in bulk.

Please consult your local CFR Sales representative for technical support or further product inquiries.