

Paraffin Solvent

PHYSICAL DESCRIPTION

Appearance	Clear, Light Orange, free-flowing liquid
Freezing Point	< -40°C
Flash Point	-30°C (PMCC)
Specific Gravity	0.65 – 0.76
Solubility	Oil – Soluble
Odour	Hydrocarbon

PROPERTIES

StaSolv™ 200 is a specialized paraffin solvent formulated with aromatic and aliphatic solvents

StaSolv™ 200 can be used to aid in cleaning up sludge and emulsions, workover fluids or as a heavy crude oil diluent.

StaSolv™ 200 will not alter natural wettability within downhole formations.

BENEFITS

StaSolv™ 200 primarily functions to remove paraffin deposits that collect on both down hole and surface production equipment.

StaSolv™ 200 is also a capable degreaser, leading to further cleaning of down hole and surface production equipment.

Paraffin Solvent

MIXING & HANDLING INSTRUCTIONS

StaSolv™ 200 should be applied in neat form

StaSolv™ 200 is designed to remove and disperse paraffinic deposits.

StaSolv™ 200 can be applied on a continuous basis or batch application.

For maximum effectiveness, a shut period is recommended to assist in maximum paraffinic deposit removal if a batch application is used.

Improved overall stimulations will result when used in conjunction with a CFR Dispersant and Wax Inhibitor Package.

CAUTION

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation and causes eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Handle with care as with any industrial chemical.

Before using this product refer to the Safety Data Sheet for all safety and handling information.

StaSolv™ 200 is available in 20L pails, 205L drums, 1000L totes and in bulk.

Please consult your local CFR Sales representative for technical support or further product inquiries.