

StaSolv SI 114

Date of Revision: February 24, 2020

Section 1 - Chemical Product and Company Identification

Product Name StaSolv SI 114
Synonyms StaSolv SI 114 2.0

Product Use Wax Solvent, Dispersant

Restriction on UseNone identified **Manufacturer/Supplier**CFR Chemicals

38451 Range Road 22

County of Red Deer T4E 2N6

General Assistance 1 (877) 269-3419

Emergency Telephone 613-966-6666 (CANUTEC 24 Hour Phone Number)

Date of Preparation of SDS April 1, 2017

Section 2 – Hazard Identification

Signal Word GHS Pictogram(s)

Danger



Target Organs Narcotic Effects

Hazard Statement:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 + H320 Causes skin irritation and causes eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life

Precautionary Statement

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surface, sparks, open flames and other ignition sources.

No smoking

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting and all material-handling

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.



StaSolv SI 114

Date of Revision: February 24, 2020

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

Response

P321 Specific Treatment: see response statements on the label P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE / DOCTOR.

P331 DO NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminate clothing. Rinse skin

with water / shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 If exposed or concerned: get medical advice / attention.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam to extinguish.

Storage

P403 + P233 Store in well-ventilated place. Keep contained tightly closed.

P403 + P235 Store in well-ventilated place. Keep cool.

P405 Store locked up.

Disposal

P501 Dispose of contents/container to an approved waste disposal unit.

GHS Classification Flammable liquids (Category 2)

Acute toxicity, dermal (Category 4)
Acute toxicity, inhalation (Category 4)
Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2B)

Carcinogenicity (Category 2)

Specific target organ toxicity - single exposure (Category 3 narcotic effects)

Specific target organ toxicity - repeated exposure: Oral (Category 2)

Aspiration hazard (Category 1)

Hazardous to the aquatic environment, acute hazard (Category 2)

HMIS Classification

Health Hazard 2
Chronic Health Hazard *
Flammability 3
Physical Hazards 0

Potential Health Effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation.

Skin May be harmful if absorbed through skin.

Eye Causes eye irritation.

Ingestion May be harmful if swallowed.



StaSolv SI 114

Date of Revision: February 24, 2020

Section 3 – Composition Information on Ingredients

HAZARDOUS INGREDIENT	Hazardous Ingradient Synonyms	PERCENT	CAS NUMBER
	Hazardous Ingredient, Synonyms		0.101101112111
Petroleum Distillate Light	Not available	10 – 30%	8002-05-9
n-hexane	n-hexane, normal-Hexane; Hexyl hydride; n- Hexylhydride; n-Caproylhydride; Hexane, normale	10 – 20%	110-54-3
Hexane, other isomers	Hexanes	10 – 20%	*
Xylene (o, m, p isomers)	Xylenes; Xylol; methyl toluene, benzene, dimethyl-; dimethylbenzene.	12 – 30%	1330-20-7
Heptane	n-heptane, normal-heptane, heptyl hydride	4 – 20%	142-82-5
Methylcyclopentane	Methyl cyclopentane, methylpentamethylene	4 – 20%	96-37-7
Sweetened Middle Distillate	Distillates (petroleum), sweetened middle; Sweetened middle distillate; Sweetened middle petroleum distillates	10 – 15%	64741-86-2
Ethylbenzene	Ethylbenzol; Phenylethane: alpha-Methyltoluene	0.4 – 10%	100-41-4
2-Ethylhexanol	2-Ethyl-1-hexanol, Isooctanol, Isooctyl Alcohol	2 – 8%	104-76-7
Monoisopropylamine Sulfonate	Not available	2 – 5%	26264-05-1
Cyclohexane	Hexamethylene; Hexahydrobenzene; Hexanaphthene * = Various ** = Mixture *** = Proprietary	1 – 5%	110-82-7
Chemical Formula	not applicable		

Section 4 - First Aid Measures

Inhalation

Move victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that vas of vapour is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison centre or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as collar, tie, belt or waistband.

Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower lids. Check for and remove contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shows. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Get medical attention immediately. Call a poison control centre or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so vomit does not enter the lungs. Never give anything by



StaSolv SI 114

Date of Revision: February 24, 2020

mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as collar, tie, belt or waistband.

Most Important Symptoms/Effects

Acute No data available.
Delayed No data available.

Note to Physician Treat symptomatically.

Section 5 – Fire-Fighting Measures

Flash Point (°C) -30°C Flash Point Method PMCC

Auto Ignition Temperature Not available.

Conditions of Flammability Flammable in the presence of a source of ignition when the temperature is above

the flash point. Keep away from heat/sparks/open flame/ hot surface. No

smoking.

Unsuitable Extinguising Media Water streams or jet.

Unusual Fire/

Explosion Hazard No data available.

Hazardous Combustion

Products Carbon oxides

Special Protective Equipment and

Precautions for Firefighters Wear appropriate protective equipment and self-contained breathing apparatus

with a full face-piece operated in positive pressure mode.

Section 6 – Accidental Release Measures

Personal precautions Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure

adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter

drains. Discharge into the environment must be avoided.

Methods and materials for

containment and cleaning up Contain free liquid if possible. Pick up by covering with an activated carbon

absorbent or other suitable inert absorbent material (e.g. sand, sawdust, generalpurpose binder). Take up & place in closed containers. Ventilate area & wash spill site after material pickup is complete. Contain and dispose of wash water in

accordance with local regulations.

Section 7 - Handling and Storage

Precautions for safe handling Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away

from sources of ignition - No smoking. Take measures to prevent the build-up of

electrostatic charge.



StaSolv SI 114

Date of Revision: February 24, 2020

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place.

Incompatible Conditions Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents. Reducing agents. Acids. Alkalis.

Section 8 – Exposure Controls / Personal Protection

Occupational Exposure Limits

Ingredient Name Exposure Limits

n-hexane Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 50ppm

ACGIH TLV (USA, 4/2014). Absorbed through skin.

TWA: 50ppm 8 Hours

Hexane, other isomers Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 500ppm

Xylene (o, m, p isomers) Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 100ppm, 435 mg/m³ 8 Hours STEL: 150ppm, 651 mg/m³ 15 minutes

Heptane Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 400ppm, 1640 mg/m³ 8 Hours STEL 500ppm, 2050 mg/m³ 15 min

Methylcyclopentane ACGIH TLV (USA, 4/2014).

TWA: 500ppm, 1760 mg/m³ 8 Hours STEL: 1000ppm, 1050 mg/m³ 15 minutes

Sweetened Middle Distillate ACGIH

TWA: 200 mg/m³ 8 Hours

OSHA PEL

TWA: 200 mg/m³

Ethylbenzene ACGIH

TWA: 20ppm 8 Hours STEL: 10000 ppm 15 minutes

OSHA PEL

TWA: 100 ppm, 435 mg/m³

2-Ethylhexanol Not Established Monoisopropylamine Sulfonate Not Established

Cyclohexane Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)).

TWA: 100ppm, 344 mg/m³ 8 Hours

Personal protective equipment

Eye/face protection Chemical safety glasses with side shields to prevent eye contact. As a general rule

do not wear contact lenses when handling chemicals.

Skin protection Wear chemical resistant gloves, impermeable protective clothing and safety

shoes.

Respiratory protection

General hygiene

Use NIOSH approved respirators and components.

Considerations Handle in accordance with good industrial hygiene and safety.

Specific engineering controls Use mechanical exhaust or laboratory fumehood to avoid exposure. Safety

shower, eye wash, and fire extinguisher should be present.

Section 9 - Physical and Chemical Properties

Physical State Liquid Water Solubility Insoluble



StaSolv SI 114

Date of Revision: February 24, 2020

Appearance & Odour Clear, Pale orange to amber. Boiling Point 66°C

Distinct odour.

Vapour PressureNot availableBoiling RangeNot available

Odour ThresholdNot availableMelting Point-30°CEvaporation RateNot availableFreezing Point-30°C

Vapour Density>1 (Air = 1)Lower Explosive Limit (LEL)Not availableSpecific Gravity0.77 – 0.81Upper Explosive LimitNot available

(UEL)

pH Not available Partition coefficient (n- Not available

octonal/water)

Flash Point (Method) -30°C (PMCC) Autoignition Temperature Not available

Flammability (Solid, Gas) Not applicable

Decomposition Not available **Viscosity** Not available

Temperature

Section 10 - Stability and Reactivity

Reactivity Heating may cause fire.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous Under normal conditions of storage and use, hazardous reactions will not occur

reactions

Conditions to avoid Heat, flames and sparks. **Materials to avoid** Oxidizing materials.

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon

oxides.

Other decomposition products - No data available

Section 11- Toxicological Information

Information on Likely Routes of Exposure

Inhalation:

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact

Prolonged or frequent contact may cause redness, itching, eczema and skin cracking. Defats the skin.

Eye contact

Causes eye irritation.

Eye contact

May irritate and cause redness and pain.

Ingestion

Ingestion of large amounts may cause unconsciousness. However, ingestion may cause nausea, headache, dizziness and intoxication. Ingestion may cause irritation of the gastrointestinal tract, vomiting and diarrhea. May cause irritation to the mouth and throat.

Acute and Chronic Toxicity

No data available

Acute toxicity

Product/Ingredient Name Result Species Dose Exposure

PAGE 6 of 9



StaSolv SI 114

Date of Revision: February 24, 2020

n-Hexane LC50 Inhalation gas Rat 48000ppm 4 Hr LD50 Oral Rat 15840mg/kg -Hexane, other isomers LC50 Inhalation gas Rat 48000ppm 4 Hr

Xylene LC50 Inhalation gas Rat 6350ppm 4 Hr

LD50 Oral Rat 3253mg/kg -LD50 Dermal Rabbit 12126mg/kg 24 Hr

HeptaneLD50 DermalRabbit>2000mg/kg-LD50 OralRat>5000mg/kg-EthylbenzeneLD50 OralRat5.46g/kg-

LD50 Dermal Rabbit >5000mg/kg -

2-Ethylhexanol LD50 Oral Rat 3730mg/kg - LD 50 Dermal Rabbit >3000mg/kg -

Monoisopropylamine Sulfonate Not determined

Cyclohexane LC50 Inhalation Vapour Mouse 70000mg/m³ 2 Hr

LD50 Oral Rat >5000mg/kg -

Conclusion n-hexane: n-hexane is a CNS depressant and narcosis at elevated concentrations.

Heptane: heptane is a CNS depressant and narcosis at elevated concentrations.

Cyclohexane: cyclohexane is a CNS depressant and narcosis at elevated

concentrations.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

Respiratory or skin sensitization

No data available Not assigned.

Carcinogenicity Suspected of causing cancer.

IARC:

Mutagenicity

Ethylbenzene 2B Possibly carcinogenic to humans

Xylene (o, m, p isomers) 3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity Not assigned.

Teratogenicity No known significant effects or critical hazards. **Specific target organ toxicity - single exposure (Globally Harmonized System)**

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Short Term Exposure

Potential immediate Health Effects No data available.

Potential Delayed Health Effects No data available.

Long Term Exposure

Potential immediate Health Effects

Potential Delayed Health Effects

Potential Chronic Effects

No data available.

No data available.

Synergistic effects No data available



StaSolv SI 114

Date of Revision: February 24, 2020

Section 12 - Ecological Information

Toxicity	

Product / Ingredient Name	Result	Species	Exposure
n-hexane	Acute LC50 2500μg/L Fresh Water	Fish – Pimephales promelas	96 Hr
Heptane	Acute EC50 1.5mg/L	Daphnia – Daphnia magna	48 Hr
	Acute LC50 4mg/L	Fish – Carassius auratus	24 Hr
Xylene (o, m, p isomers)	Acute LC50 13.1 - 16.5mg/L	Fish – Lepomis macrochirus	96 Hr
	Acute LC50 13.5 – 17.3mg/L	Fish – Oncorhynchus mykiss	96 Hr
Ethylbenzene	Acute LC50 4mg/L	Fish – Oncorhynchus mykiss	96 Hr
	Acute EC50 1 – 4mg/L	Daphnia – Daphnia magna	48 Hr
2-Ethylhexanol	Acute LC50 17.1mg/L	Fish – Leuciscus idus	96 Hr
	Acute EC50 14mg/L	Daphnia – Daphnia magna	48 Hr
Isopropylamine Sulfonate	No data available		
Cyclohexane	Acute LC50 4530μg/L Fresh Water	Fish – Pimephales promelas	96 Hr

Persistence and degradability

Biodegradability No data available

Bioaccumulative potential

Product/Ingredient Name	LogPow	BCF	Potential
n-hexane	4	502	High
Xylene (o, m, p isomers)	3.2	Not available	Not available
Heptane	4.66	552	High
Methylcyclopentane	3.37	-	Low
Ethylbenzene	3.15	Not available	Not available
2-Ethylhexanol	Not available	Not available	Not available
Cyclohexane	3.44	167	low

Mobility in soilNo data availablePBT and vPvB assessmentNo data available

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional

handling or disposal. 2-Ethylhexanol is harmful to aquatic life.

Section 13 - Disposal Considerations

Product This combustible material may be burned in a chemical incinerator equipped with

an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service

to dispose of this material.

Contaminated packaging Dispose of as unused product.

Section 14 - Transportation Information

CANADA Transportation of Dangerous Goods (TDG)

Shipping Name UN1268, PETROLEUM DISTILLATES, N.O.S. (Naptha Solvent), 3. PG II

Class 3
UN Number UN1268
Packaging Group:

Label





StaSolv SI 114

Date of Revision: February 24, 2020

Reportable Quantity 12345.7 lbs / 5604.9Kg [2177.5 gal / 8242.6L]

Not a marine pollutant.

Package sizes shipped in quantities less than the product reportable quantity are

not subject to the RW transportation requirements.

Environmental hazards

Transportation in bulk,

if applicableNo data availableSpecial PrecautionsNo data available

Section 15 – Regulatory Information

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act)

All components of this product are in compliance with the chemical notification

requirements of the NSN Regulations under CEPA, 1999.

TSCA Inventory 12(b) All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Section 16 – Other Information

REVISION SUMMARY:

Date of Preparation April 1, 2017
Date of Revision February 24, 2020

SDS Prepared by: CFR Lab Manager

CFR Chemicals Inc. provides the information contained herein in good faith, but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. CFR Chemicals Inc. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, CFR CHEMICALS INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OR RELIANCE UPON THIS INFORMATION.