

UltraSol 100

Paraffin Solvent

PHYSICAL DESCRIPTION

Appearance	Dark Orange to Brown, free-flowing liquid
Freezing Point	< -40°C
Flash Point	-49°C (PMCC)
Specific Gravity	0.65 – 0.75
Solubility	Oil – Soluble
Odour	Hydrocarbon

PROPERTIES

UltraSol 100 is an economic, value-added product blend containing a specific refined condensate that has been enhanced with wetting surfactants and crystal modifiers.

UltraSol 100 contains approximately 16% aromatics, with the remainder composing short-chain aliphatic and cyclic hydrocarbons.

UltraSol 100 will not alter natural wettability within downhole formations.

BENEFITS

UltraSol 100 is designed for a multitude of uses aside from wax reduction and remediation: a cost-effective workover fluid, sludge removal, tank bottoms reduction and removal, heavy crude oil diluents.

UltraSol 100

Paraffin Solvent

MIXING & HANDLING INSTRUCTIONS

UltraSol 100 is designed for use in batch applications.

For maximum effectiveness, a shut period is recommended to assist in maximum paraffinic deposit removal if a batch application is used.

Improved overall stimulations will result when used in conjunction with a CFR Dispersant and Wax Inhibitor Package.

CAUTION

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation and causes eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Handle with care as with any industrial chemical.

Before using this product refer to the Safety Data Sheet for all safety and handling information.

UltraSol 100 is available in 20L pails, 205L drums, 1000L totes and in bulk.

Please consult your local CFR Sales representative for technical support or further product inquiries.