

UltraSol 50

Paraffin Solvent

PHYSICAL DESCRIPTION

Appearance	Dark Orange to Brown, free-flowing liquid
Freezing Point	< -40°C
Flash Point	-5°C (PMCC)
Specific Gravity	0.72 – 0.82
Solubility	Oil – Soluble
Odour	Hydrocarbon

PROPERTIES

UltraSol 50 is an economic product containing a specific refined condensate

UltraSol 50 contains approximately 15% aromatics, with the remainder composing short-chain aliphatic and cyclic hydrocarbons.

UltraSol 50 will not alter natural wettability within downhole formations.

BENEFITS

UltraSol 50 is designed for a multitude of uses aside from wax reduction and remediation: a cost-effective workover fluid, sludge removal, tank bottoms reduction and removal, heavy crude oil diluents.

UltraSol 50

Paraffin Solvent

MIXING & HANDLING INSTRUCTIONS

UltraSol 50 is designed for use in batch applications.

For maximum effectiveness, a shut period is recommended to assist in maximum paraffinic deposit removal if a batch application is used.

Improved overall stimulations will result when used in conjunction with a CFR Dispersant and Wax Inhibitor Package.

CAUTION

Highly flammable liquid and vapour. Causes skin irritation and causes eye irritation. May cause damage to organs through prolonged or repeated exposure.

Handle with care as with any industrial chemical.

Before using this product refer to the Safety Data Sheet for all safety and handling information.

UltraSol 50 is available in 20L pails, 205L drums, 1000L totes and in bulk.

Please consult your local CFR Sales representative for technical support or further product inquiries.