

# UltraSol SI

---

## Paraffin Solvent & Oil Soluble Scale Inhibitor

### PHYSICAL DESCRIPTION

Appearance	Dark Orange to Brown, free-flowing liquid
Freezing Point	< -40°C
Flash Point	-5°C (PMCC)
Specific Gravity	0.76 – 0.80
Solubility	Oil – Soluble
Odour	Hydrocarbon

### PROPERTIES

UltraSol SI is an oil-based scale inhibitor that is formulated using a specific refined condensate

UltraSol SI will not alter natural wettability within downhole formations.

### BENEFITS

UltraSol SI functions to help remove paraffin deposits that can collect on both downhole and surface production equipment. This product also prevents formation of scale deposits, which can act as nucleation sites for wax deposits.

UltraSol SI is designed for a multitude of uses aside from wax reduction and remediation: a cost-effective workover fluid, sludge removal, tank bottoms reduction and removal, heavy crude oil diluents.

# UltraSol SI

---

## Paraffin Solvent & Oil Soluble Scale Inhibitor

### MIXING & HANDLING INSTRUCTIONS

UltraSol SI should be applied in neat form.

UltraSol SI is best applied on a continuous injection basis, with typical rates being 1-2 L of product per cube of fluid.

UltraSol SI can be batched – CFR Chemicals would ask that production be provided so a batch volume can be recommended.

Improved overall stimulations will result when used in conjunction with a CFR Dispersant and Wax Inhibitor Package.

### CAUTION

Highly flammable liquid and vapour. Causes skin irritation and causes eye irritation. May cause damage to organs through prolonged or repeated exposure.

Handle with care as with any industrial chemical.

Before using this product refer to the Safety Data Sheet for all safety and handling information.

UltraSol SI is available in 20L pails, 205L drums, 1000L totes and in bulk.

Please consult your local CFR Sales representative for technical support or further product inquiries.