

Date of Revision: March 15, 2022

Section 1 - Chemical Product and Company Identification

Product Name UltraSol 55

Synonyms Enhanced Condensate **Product Use** Solvent, heavy oil diluent

Restriction on UseNone identified **Manufacturer/Supplier**CFR Chemicals

38451 Range Road 22

County of Red Deer T4E 2N6

General Assistance 1 (877) 269-3419

Emergency Telephone 613-966-6666 (CANUTEC 24 Hour Phone Number)

Date of Preparation of SDS January 10, 2020

Section 2 - Hazard Identification

Signal Word GHS Pictogram(s)

Danger



Target Organs Peripheral nervous system, Kidney, Testes.

Hazard Statement:

H225 Highly flammable liquid and vapour.

H315 + H320 Causes skin irritation and causes eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure if

swallowed or inhaled.

Precautionary Statement

P210 Keep away from heat, hot surface, sparks, open flames and other ignition sources.

No smoking

P233 Keep container tightly closed.

P240 Ground/Bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting and all material-handling

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/eye protection/face protection.

Response

P321 Specific treatment: See Response Statements on this label.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminate clothing. Rinse skin

with water / shower.



Date of Revision: March 15, 2022

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P314 Call a POISON CENTRE or doctor/physician if you feel unwell
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam to extinguish

Storage

P403 + P233 Store in well-ventilated place. Keep contained tightly closed.

P403 + P235 Store in well-ventilated place. Keep cool

P405 Store locked up.

Disposal

P501 Dispose of contents/container to an approved waste disposal unit.

GHS Classification Flammable liquids (Category 2)

Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2B)

Specific target organ toxicity - repeated exposure: Oral (Category 2)
Specific target organ toxicity - repeated exposure: Inhalation (Category 2)

HMIS Classification

Health Hazard 2
Chronic Health Hazard *
Flammability 3
Physical Hazards 0

Potential health effects

Inhalation Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May

cause respiratory tract irritation.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed – can enter lungs and cause damage.

Skin May be harmful if absorbed through skin. May cause skin irritation.

Eyes May cause eye irritation.

Section 3 – Composition Information on Ingredients

| HAZARDOUS INGREDIENT Natural Gas Condensate | Hazardous Ingredient, Synonyms Not available | PERCENT 90 - 99% | CAS NUMBER 8002-05-9 | |
|--|--|-------------------------|-----------------------------|--|
| Heavy Catalytic Reformed Naptha (petroleum) | Heavy aromatic naptha; Heavy aromatic naptha, gasoline re-run overhead; Aromatic hydrocarbon $0-5$ mixture | | 64741-68-0 | |
| This product may also contain | | | | |
| Toluene | benzyl hydride; methylbenzene; phenylmethane; toluol. | 0-10 | 108-88-3 | |
| Xylene, mixed isomers | Xylenes; Xylol; methyl toluene, benzene, dimethyl-; dimethylbenzene. | 0-10 | 1330-20-7 | |
| Hexanes | n-hexane, normal-Hexane; Hexyl hydride; n- Hexylhydride; n-Caproylhydride; Hexane, normale | 0-5 | 100-54-3 | |



Date of Revision: March 15, 2022

Benzene Benzol, 0-5 71-43-2
Ethylbenzene Ethylbenzol; Phenylethane: alpha-Methyltoluene 0-1 100-41-4

1,2,4-trimethylbenzene Pseudocumene, pseudocumol 0-1.1 25551-13-7

* = Various ** = Mixture *** = Proprietary

Chemical Formula mixture

Section 4 - First Aid Measures

Inhalation Move victim to fresh air and keep at rest in a position comfortable for breathing.

If it is suspected that vas of vapour is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison centre or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as collar, tie, belt or waistband.

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and

lower lids. Check for and remove contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Skin Contact Flush contaminated skin with plenty of water. Remove contaminated clothing and

shows. Continue to rinse for at least 10 minutes. Get medical attention. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion Get medical attention immediately. Call a poison control centre or physician.

Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight

clothing such as collar, tie, belt or waistband.

Most Important Symptoms/Effects

Acute

Eye contact Causes eye irritation.

Inhalation Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact No known significant effects or critical hazards.

Ingestion Can cause central nervous system (CNS) depression.

Delayed

Eye contact No specific data.

Inhalation Adverse symptoms may include the following:, nausea or vomiting, headache,

drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight,

increase in fetal deaths, skeletal malformations

Skin contact Adverse symptoms may include the following:, reduced fetal weight, increase in

fetal deaths, skeletal malformations



Date of Revision: March 15, 2022

Ingestion Adverse symptoms may include the following:, reduced fetal weight, increase in

fetal deaths, skeletal malformations

Note to Physician Treat symptomatically.

Section 5 – Fire-Fighting Measures

Conditions of Flammability Flammable in the presence of a source of ignition when the temperature is above

the flash point. Keep away from heat/sparks/open flame/ hot surface.

Extinguishing MediaUse water spray (fog), alcohol-resistant foam, dry chemical or carbon dioxide

Unsuitable Extinguising Media Do not use water jet.

Unusual Fire/

Explosion Hazard No data available.

Hazardous Combustion

Products Carbon oxides, Nitrogen oxides, sulfur oxides, dense smoke and particulate

matter.

Fire Fighting Equipment Wear appropriate protective equipment and self-contained breathing apparatus

with a full face-piece operated in positive pressure mode.

Section 6 – Accidental Release Measures

Personal precautions Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure

adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe

areas. Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter

drains. Discharge into the environment must be avoided.

Methods and materials for

containment and cleaning up Stop leak if without risk. Move containers from spill area. Use spark-proof tools

and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Section 7 – Handling and Storage

Precautions for safe handling Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away

from sources of ignition - No smoking. Take measures to prevent the build-up of

electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place.

Incompatible Conditions

Heat, flames and sparks.

Incompatible Materials Oxidizing materials, strong acids.

Section 8 – Exposure Controls / Personal Protection

Occupational Exposure Limits

Ingredient Name Exposure Limits



Date of Revision: March 15, 2022

Toluene Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 50ppm ACGIH TLV TWA: 20ppm

STEL: 20ppm OSHA PEL

TWA: 200 ppm STEL: 500 ppm

Xylene (o, m, p isomers) Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 100ppm STEL: 150ppm

Hexanes Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 50ppm

Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 0.5ppm, 1.6mg/m³ Ceiling: 2.5ppm, 8mg/m³

Ethylbenzene ACGI

TWA: 20ppm 8 Hours STEL: 10000 ppm 15 minutes

OSHA PEL

TWA: 100 ppm TWA: 435 mg/m³

1,2,4-trimethylbenzene Canada, Alberta, Occupational Health and Safety Cote (table 2: OEL)

TWA: 25ppm

Personal protective equipment

Benzene

Eye/face protection Chemical safety glasses with side shields to prevent eye contact. As a general rule

do not wear contact lenses when handling chemicals.

Skin protection Wear chemical resistant gloves, impermeable protective clothing and safety

shoes.

-5° (PMCC)

Respiratory protection

General hygiene

Flash Point

Use NIOSH approved respirators and components.

Considerations Handle in accordance with good industrial hygiene and safety.

Specific engineering controls Use mechanical exhaust or laboratory fumehood to avoid exposure. Safety

shower, eye wash, and fire extinguisher should be present.

Section 9 - Physical and Chemical Properties

| Physical State | Liquid | Water Solubility | Insoluble |
|------------------------------|--|---|----------------|
| Appearance & Odour | Clear colourless to pale brown liquid with distinct hydrocarbon odour. | Boiling Point | 52.5°C |
| Vapour Pressure | Varies with feedstock. | Boiling Range | 52.5°C – 100°C |
| Odour Threshold | Not available | Melting Point | <-40°C |
| Evaporation Rate | Not available | Freezing Point | <-40°C |
| Vapour Density | >1 (Air = 1) | Lower Explosive Limit (LEL) | Not available |
| Specific Gravity | 0.74 – 0.765 | Upper Explosive Limit (UEL) | Not available |
| рН | Not available | Partition coefficient (n- octonal/water) | Not available |
| Flammability (Solid, Gas) | Not available | | |
| Decomposition Temperature | Not available | Viscosity | Not available |

Auto-ignition temperature

>400°C



Date of Revision: March 15, 2022

Section 10 – Stability and Reactivity

Reactivity No specific test data related to reactivity available for this product or its

ingredients.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous

reactions

Conditions to avoid Heat, flames and sparks.

Materials to avoid Oxidizing materials, strong acids.

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon

oxides, Nitrogen oxides, sulfur oxides.

Other decomposition products – May release carbon oxides, aldehydes, ketones,

Under normal conditions of storage and use, hazardous reactions will not occur

reactive hydrocarbons, smoke and irritating vapors when heated to

decomposition.

Section 11- Toxicological Information

Information on Likely Routes of Exposure

No data available

Acute toxicity

| Product/Ingredient Name | Result | Species | Dose | Exposure |
|--------------------------|---------------------|---------|------------------------|----------|
| Toluene | LC50 Inhalation gas | Rat | >20mg/L | 4 Hr |
| | LD50 Oral | Rat | 5580mg/kg | - |
| | LD50 Dermal | Rabbit | 12223mg/kg | - |
| Xylene (o, m, p isomers) | LC50 Inhalation gas | Rat | 6350ppm | 4 Hr |
| , , , , , , , , | LD50 Oral | Rat | 3253mg/kg | - |
| | LD50 Dermal | Rabbit | 12126mg/kg | 24 Hr |
| Hexanes | LC50 Inhalation gas | Rat | 48000ppm | 4 Hr |
| | LD50 Oral | Rat | 15840mg/kg | - |
| | LC50 Inhalation gas | Rat | 13700ppm | 4 H4 |
| Benzene | LD50 Oral | Rat | 4920mg/kg | - |
| | LD50 Dermal | Rabbit | >8240mg/kg | - |
| Ethylbenzene | LD50 Oral | Rat | 5.46g/kg | - |
| | LD50 Dermal | Rabbit | >5000mg/kg | - |
| 1,2,4-trimethylbenzene | LC50 Inhalation gas | Rat | 18000mg/m ³ | 4 Hr |
| | LD50 Oral | Rat | 50000mg/kg | - |

Skin corrosion/irritation Causes skin and eye irritation.

Respiratory or skin sensitization

No data available

Mutagenicity Xylene and Toluene have been investigated as mutagens. There has been some evidence

of chromosomal changes in workers exposed to benzene.

Carcinogenicity Components are suspected of causing cancer.

IARC:

Benzene 1 Carcinogenic to Humans

PAGE 6 of 9



Date of Revision: March 15, 2022

Ethylbenzene 2B Possibly carcinogenic to Humans

Reproductive toxicity
Not available
Teratogenicity
Not available
Specific target organ toxicity - single exposure

This product is not reported to have any specific target organ general toxicity

single exposure effects.

Specific target organ toxicity - repeated exposure

Causes damage to organs (liver, kidneys, blood, nervous system and skin) through

prolonged or repeated exposure.

Aspiration hazard Aspiration may result in chemical pneumonia, severe lung damage, respiratory

failure and even death.

Potential health effects

Inhalation Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May

cause respiratory tract irritation.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed – can enter lungs and cause damage.

Skin May be harmful if absorbed through skin. May cause skin irritation.

Eyes May cause eye irritation.

Signs and Symptoms of Exposure

Inhalation Adverse symptoms may include: nausea and vomiting, headache, drowsiness/fatigue,

dizziness/vertigo and unconsciousness

Ingestion Adverse symptoms may include: nausea and vomitingSkin Adverse symptoms may include: irritation, redness

Eyes Adverse symptoms may include: pain or irritation, watering, redness

Synergistic effects No data available

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Short Term Exposure

Potential immediate Health Effects No data available.

Potential Delayed Health Effects No data available.

Long Term Exposure

Potential immediate Health Effects
Potential Delayed Health Effects
Potential Chronic Effects
No data available.
No data available.

Section 12 – Ecological Information

Toxicity

| Prod | luct / Ingredient Name | Result | Species | Exposure |
|------|------------------------|---------------------------------|----------------------------|----------|
| Tolu | ene | Acute LC50 24mg/L | Fish – Onchohynchus mykiss | 96 Hr |
| | | Acute EC50 84mg/L | Daphnia – Daphnia magna | 24 Hr |
| | | Acute LC50 13mg/L | Fish – Lepomis macrochirus | 96 Hr |
| Xyle | ne (o, m, p isomers) | Acute LC50 13.1 - 16.5mg/L | Fish – Lepomis macrochirus | 96 Hr |
| | | Acute LC50 13.5 – 17.3mg/L | Fish – Oncorhynchus mykiss | 96 Hr |
| Hexa | anes | Acute LC50 2500μg/L Fresh Water | Fish – Pimephales promelas | 96 Hr |
| Benz | zene | | | |
| Ethy | lbenzene | Acute LC50 4mg/L | Fish – Oncorhynchus mykiss | 96 Hr |



Date of Revision: March 15, 2022

Acute EC50 1 – 4mg/L Daphnia – Daphnia magna 48 Hr Acute LC50 10.7 -14.7mgL Fish – Pimephales promelas 96 Hr

1,2,4-trimethylbenzene **Persistence and degradability**

Biodegradability No data available

Bioaccumulative potential

Product/Ingredient NameLogPowBCFPotentialn-hexane4502High

Mobility in soilNo data availablePBT and vPvB assessmentNo data available

Other adverse effects No known significant effects or critical hazards.

Section 13 - Disposal Considerations

Product This combustible material may be burned in a chemical incinerator equipped with

an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service

to dispose of this material.

Contaminated packaging Dispose of as unused product.

Section 14 - Transportation Information

CANADA Transportation of Dangerous Goods (TDG)

Shipping Name UN1268, PETROLEUM DISTILLATES, N.O.S. (condensate), 3. PG II

Class 3

UN Number UN1268

Packaging Group ||

Label



Environmental hazards

ds Not a marine pollutant.

Transportation in bulk,

if applicableNo data availableSpecial PrecautionsNo data available

Reportable Quantity 12345.7 lbs / 5604.9Kg [2177.5 gal / 8242.6L] Package sizes shipped in quantities

less than the product reportable quantity are not subject to the RW

transportation requirements.

Section 15 - Regulatory Information

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act)

All components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.



Date of Revision: March 15, 2022

TSCA Inventory (8b) All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Section 16 – Other Information

REVISION SUMMARY:

Date of Preparation January 10, 2020 Date of Revision March 15, 2022

SDS Prepared by: CFR Lab Manager

CFR Chemicals Inc. provides the information contained herein in good faith, but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. CFR Chemicals Inc. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, CFR CHEMICALS INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OR RELIANCE UPON THIS INFORMATION.