

Packer Fluid Inhibitor

PHYSICAL DESCRIPTION

Appearance	Opaque, Dark Brown, free flowing liquid
Specific Gravity	1.00– 1.03
Solubility	Water, Alcohol
Odour	Amine
pH	8.0 – 9.0 (5% v/v)

PROPERTIES

CPF-103 is a proprietary water soluble formulation that provides excellent corrosion control for batching into existing annular fluids.

CPF-103 is a preventative treatment to inhibit corrosion caused by oilfield brines, organic acids, oxygen and carbon dioxide.

CPF-103 is formulated with filming components and neutral surfactants to effectively cover a surface.

BENEFITS

CPF-103 is a field proven packer fluid inhibitor that has excellent ease of use for personnel.



CPF-103

Packer Fluid Inhibitor

MIXING & HANDLING INSTRUCTIONS

CPF-103 mixes uniformly in water and should be applied at a rate of 5000 to 10000 ppm (5 to 10L per m³)

CAUTION, SHIPPING & HANDLING

Flammable liquid and vapour. Causes skin irritation, Causes serious eye irritation. Toxic if swallowed, in contact with skin, or inhaled. Causes damage to organs.

Handle with care as with any industrial chemical.

Wash contacted area with large quantities of water.

CPF-103 is available in 20 Liter pails, 205 Liter drums and in bulk.

Safety Data Sheets are available outlining safe handling practices.

Disposal should be in accordance with all applicable federal, provincial, and local environmental regulations and laws.

For additional assistance or information, please contact your nearest CFR Chemicals Representative