

Hexanes

Specific Gravity	0.6650 - 0.6760 _{20/20}
Refractive Index	1.3750 - 1.3850 ₂₀
Moisture (max.)	0.005% (50 ppm)
Distillation Range	52.7°C – 94.6°C
Appearance	Clear, n.s.m.
Colour (max.)	5 (ASTM, PtCo)

Shipping and Handling

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation and causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if swallowed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep containers closed when not in use, and store in a cool area. Avoid breathing mist and vapour. Use explosion proof electric equipment, and ensure proper electrical grounding procedures are followed when handling this product. Wash skin thoroughly after handling. Do not eat, drink, or smoke when using this product. Wear protective gloves and eye/face protection.

Refer to Safety Data Sheets (SDS) before handling.

Hexanes are available in bulk, 1000 L totes, or 205L drums.

Disposal should be in accordance with all applicable federal, provincial, and local environmental regulations and laws.

For additional assistance or information, please contact your nearest CFR Chemical Representative.