

Sales Specifications

Isopropyl Alcohol, Technical Grade

*Better People.
Better Service.*



Purity (min)	99.9%
Specific Gravity	0.7850 - 0.7860
Moisture (max.)	2000 ppm / 0.2%
Acidity (acetic acid) max.	0.002%
Appearance	Bright, n.s.m
Colour (ASTM, PtCo) max.	10
Dilution Test*	Diluted 1:10 in water - resulting solution clear, with a "clean" alcohol odour

Shipping and Handling

Highly flammable liquid and vapour. Causes mild skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep containers closed when not in use, and store in a cool area. Avoid breathing mist and vapour. Use explosion proof electric equipment, and ensure proper electrical grounding procedures are followed when handling this product. Wash skin thoroughly after handling. Do not eat, drink, or smoke when using this product. Wear protective gloves and eye/face protection.

Refer to Safety Data Sheets (SDS) before handling.

Isopropyl Alcohol is available in bulk, 1000 L totes, or 205L drums.

Disposal should be in accordance with all applicable federal, provincial, and local environmental regulations and laws.

For additional assistance or information, please contact your nearest CFR Chemical Representative.