

## Sales Specifications

*Better People.  
Better Service.*



### Xylenes

|                           |                       |
|---------------------------|-----------------------|
| <b>Purity* (min.)</b>     | 98.0%                 |
| <b>Specific Gravity</b>   | 0.8645 - 0.869020/20  |
| <b>Refractive Index</b>   | 1.4950 - 1.498020     |
| <b>Moisture (max.)</b>    | 0.02% (200 ppm)       |
| <b>Distillation Range</b> | 138.0oC - 143.0oC     |
| <b>Appearance</b>         | Clear, bright, n.s.m. |
| <b>Colour (max.)</b>      | 10 (ASTM, PtCo)       |

### Shipping and Handling

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause cancer. Vapours may form explosive mixtures with air. Product should be kept away from sources of heat and sources of ignition. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep containers closed when not in use, and store in a cool area. Avoid breathing mist and vapour. Use explosion proof electric equipment, and ensure proper electrical grounding procedures are followed when handling this product.

Refer to Safety Data Sheets (MSDS) before handling.

Xylenes are available in bulk, 1000 L totes, or 205L drums.

Disposal should be in accordance with all applicable federal, provincial, and local environmental regulations and laws.

For additional assistance or information, please contact your nearest CFR Chemical Representative.